

"Get with The Program!"





Stain Solution #1 Treatment (the iron, cobalt & spot etching stuff™)

<u>Treatment Prerequisites</u>

- DO NOT PROCEED IF THE FOLLOWING CONDITIONS HAVE NOT BEEN MET, CONTACT JACK'S MAGIC TECHNICAL SUPPORT FOR ASSISTANCE
- Positive reaction for this treatment with Jacks Magic Stain ID Kit
- Water Temperature must be above 65
- Isolate or remove ionizers and mineral systems
- Properly balanced water for stain treatment (see chart below)

1. Balance pool water to the following parameters:

BALANCE PARAMETERS for STAIN IDENTIFICATION AND REMOVAL	
Pool Water Item:	Balance Parameter(s)
Free and Total Available Chlorine (FAC & TAC)	Less than 1 ppm
рН	7.2 or below
Total Alkalinity (TA)	80 ppm or below
Calcium Hardness (CH)	200 - 400 ppm
Cyanuric Acid (Stabalizer) (CYA)	Below 70 ppm
Total Disolved Solids (TDS)	Below 1,200 ppm (4,000 ppm in salt systems)

TIP: Use Jack's Magic after shock to quickly reduce chlorine if above 1 ppm. Add 1 ounce of after shock directly through the skimmer per 7,500 gallons of pool water to reduce chlorine by 1ppm, being careful not to overdose.

- 2. Turn pool pump on.
- 3. Add Jack's Magic the blue stuff at a rate of 1 quart per 10,000 gallons of pool water. With salt(chlorine generator) systems, use Jack's Magic the purple stuff in place of the blue stuff.
- 4. Add Jack's Magic Stain Solution #1 iron, cobalt & spot etching stuff at a rate of 2 pounds per 12,000 gallons of pool water; broadcast over stained area.
- 5. Circulate pool continuously on high speed for 24 hours.

TIP: Use the filter fiber stuff™ to enhance filtration in a sand or cartridge system for a more efficient removal

- Clean filter and wait an additional 24 to 48 before beginning to slowly re-chlorinate.
 IMPORTANT: DO NOT SHOCK for at least one week after removal. May cause re-staining of any metals/minerals that are still in solution.
- 7. To re-balance low Total Alkalinity use sodium bicarbonate only at a rate of no more than 4 pounds per 10,000 gallons per day.
- 8. Add 12 ounces of the blue stuff or the purple stuff per 10,000 gallons weekly for a minimum of three weeks after treatment.