



Jack Pacs™

Treatment #4 Pack

Includes everything needed
for Iron Scale treatment:

- (1) 2 lbs. The Iron, Cobalt & Spot Etching Stuff™
- (1) 10 lbs. The Copper & Scale Stuff™
- (2) 32 oz. The Purple Stuff®
- (1) 9 oz. The Filter Fiber Stuff™



Treats 10,000 gallons



"Get with The Program!"



Jack's stain program™

step
2

REMOVAL

Iron Scale Treatment (Iron Cobalt & Spot Etching Stuff™ and Copper & Scale Stuff™)

Treatment Prerequisites

**DO NOT PROCEED IF THE FOLLOWING CONDITIONS HAVE NOT BEEN MET
CONTACT JACK'S MAGIC TECHNICAL SUPPORT FOR ASSISTANCE**

- Positive reaction for this treatment with **Jack's Magic Stain ID Kit**
- Water Temperature must be above 65°F
- Isolate all heaters and/or heat pumps from circulation system
- Isolate or remove ionizers, mineral systems and chemical feeders; turn off salt generators
- This treatment is recommended for pools up to 35,000 gallons; contact a Jack's Magic technician for larger pools
- Properly balanced water for stain treatment (see chart below)

TIP: Do not swim during this treatment. If you cannot close the pool for the duration of an Iron Scale Treatment (48 hours – 2 weeks), contact a Jack's Magic representative for an alternative solution.

1. Balance pool water to the following parameters:

BALANCE PARAMETERS for STAIN IDENTIFICATION AND REMOVAL	
Pool Water Item:	Balance Parameter(s)
Free and Total Available Chlorine (FAC & TAC)	1-3 ppm
pH	7.0 - 7.2
Total Alkalinity (TA)	80 ppm or below
Calcium Hardness (CH)	200 - 400 ppm
Cyanuric Acid (Stabilizer) (CYA)	Below 70 ppm
Total Dissolved Solids (TDS)	Below 1,200 ppm (4,000 ppm in salt systems)

2. Turn pool pump on.

3. Add ½ gallon muriatic (pool) acid per 10,000 gallons of pool water AFTER the pH and TA are adjusted.

4. Add Jack's Magic® **The Blue Stuff®** at a rate of 1 quart per 10,000 gallons of pool water.

TIP: With salt (chlorine generator) system or high TDS (over 1,200 ppm) substitute **The Purple Stuff®** in place of **The Blue Stuff**.

5. Add 10 pounds of Jack's Magic **STAIN SOLUTION #2 The Copper & Scale Stuff™** per 10,000 gallons of pool water. Pre-dilute product in bucket or brush any undissolved product immediately as it reaches the bottom.

6. Circulate pool continuously on high speed for the duration of the treatment (48 hours – 2 weeks).

TIP: Use **The Filter Fiber Stuff™** to enhance filtration in a sand or cartridge system for a more efficient removal.